MultiPHP Manager

Ändern der PHP Version

Loggen Sie sich in Ihr cPanel Dashboard ein und tippen Sie in der Suchleiste "php" ein.
In den Suchergebnissen gehen Sie unter "Software" und klicken dort auf "MultiPHP-Manager".

> Klicken Sie bitte nicht auf "PHP Version wählen".
> Diese Funktion ist ausschließlich für den Cloudlinux PHP Selector vorbehalten.
> Falls Sie den Cloudlinux PHP Selector für Ihr Paket verwenden möchten, lesen Sie bitte hier: Cloudlinux PHP Selector



PHP Version kontrollieren

Hier sehen Sie nun die verwendete PHP Version von Ihrem Paket.
Wenn diese PHP Version gleich oder sogar unterhalb der PHP Versionsnummern ist, welche in der gelben Hinweismeldung angegeben ist, aktualisieren Sie bitte unverzüglich Ihre PHP Version.

Sollte unter PHP-Version der Wert "Inherit" gesetzt sein, wird die System-PHP-Version verwendet.
Auch dann sollten Sie Ihre PHP Version auf die aktuellste ändern, da ansonsten bei einem automatischen Update Ihre PHP Version ohne Ihr Wissen angepasst werden könnte und dadurch eventuell Teile Ihrer Website nicht mehr funktionieren könnten.



PHP Version ändern

Wählen Sie im unteren Bereich nun alle Domains auf Ihrem Packet aus, bei welcher Sie die PHP Version aktualisieren möchten.
Wählen Sie nun bitte im rechten Dropdown Menü die gewünschte neue PHP Version aus und klicken Sie auf "Übernehmen".

> ⚠ Mit Stand 01.01.2020 ist die PHP Version 7.3 (ea-php73) die beste Wahl.

> ⛔ Bitte achten Sie unbedingt darauf, eine PHP Version auszuwählen die mit ea-php* und NICHT mit alt-php* beginnt.



Wenn alles richtig gemacht wurde, steht nun eine neue PHP Version bei den ausgewählten Domains.



PHP Optionen ändern

Um für die eingestellte PHP Version nun noch PHP Optionen zu ändern, geht man zurück in das cPanel Dashboard und sucht nochmals nach "php" und klickt nun auf "MultiPHP INI-Editor".
In diesem Editor kann man nun die Basis Einstellungen ändern oder auch im Editormodus weitere Einstellungen hinzufügen.

Weiterführende Dokumentation für den Editor: https://documentation.cpanel.net/display/74Docs/MultiPHP+INI+Editor+for+cPanel


TELEMATICA
php
DATENBANKEN
phpMy Admin
SOFTWARE
PHP PEAR Pakete
MultiPHP Manager
MultiPHP INI Editor
PHP Version wählen
ALLGEMEINE INFORMATIONEN
Aktueller Benutzer
Primäre Domäne
Shared IP Address
Home-Verzeichnis
Last Login IP Address
Design
Serverinformationen
STATISTIK
MySQL®-Datenbanken
Addon-Domänen
Speicherplatznutzung
E-Mail-Konten
Dateinutzung
MySQL®-Speicherplatznutzung
Bandbreite
Unterdomänen
Aliase
Adresslisten


TELEMATICA
MultiPHP INI-Editor
The MultiPHP INI editor writes to the .htaccess, .user.ini und php.ini files. The system will only write a directive to a file if it is a valid directive for that file type. For more information, read our MultiPHP INI Editor documentation.
Basismodus
Editormodus
PHP INI-Grundeinstellungen konfigurieren
Select the home directory or a domain's document root to open the corresponding PHP configuration.
Pfad /home/tm002188/public_html/php.ini
PHP-Version ea-php73
Domäne
PHP-Anweisung
Information
Einstellung
display_errors
This determines whether errors should be printed to the screen as part of the output or if they should be hidden from the user.
Deaktiviert
max_execution_time
This sets the maximum time in seconds a script is allowed to run before it is terminated by the parser. This helps prevent poorly written scripts from tying up the server. The default setting is 90.
30
max_input_time
This sets the maximum time in seconds a script is allowed to parse input data, like POST, GET and file uploads.
60
max_input_vars
This sets the maximum number of input variables allowed per request and can be used to deter denial of service attacks involving hash collisions on the input variable names.
1000
memory_limit
This sets the maximum amount of memory in bytes that a script is allowed to allocate. This helps prevent poorly written scripts for eating up all available memory on a server. Note that to have no memory limit, set this directive to -1.
128M
post_max_size
Sets max size of post data allowed. This setting also affects file upload. To upload large files, this value must be larger than upload_max_filesize. Generally speaking, memory_limit should be larger than post_max_size.
8M
session.gc_maxlifetime
This specifies the number of seconds after which data will be seen as "garbage" and potentially cleaned up.
1440
session.save_path
session.save_path defines the argument which is passed to the save handler. If you choose the default files handler, this is the path where the files are created.
/var/cpanel/php/sessions/ea-php71
upload_max_filesize
The maximum size of an uploaded file.
16M
zlib.output_compression
Whether to transparently compress pages. If this option is set to "On" in php.ini or the Apache configuration, pages are compressed if the browser sends an "Accept-Encoding: gzip" or "deflate" header.
Deaktiviert
Übernehmen
cPanel
Home
Marken
Privacy Policy
Dokumentation
Hilfe


TELEMATICA
MultiPHP INI-Editor
The MultiPHP INI editor writes to the .htaccess, .user.ini und php.ini files. The system will only write a directive to a file if it is a valid directive for that file type. For more information, read our MultiPHP INI Editor documentation.
Basismodus
Editormodus
PHP INI-Einstellungen bearbeiten
Select the home directory or a domain's document root to open the corresponding PHP configuration.
Speichern
Pfad /home/tm002188/public_html/php.ini
PHP-Version ea-php73
Domäne
; cPanel-generated php ini directives, do not edit
; Manual editing of this file may result in unexpected behavior.
; To make changes to this file, use the cPanel MultiPHP INI Editor (Home >> Software >> MultiPHP INI Editor)
; For more information, read our documentation (https://go.cpanel.net/EA4ModifyINI)
display_errors = Off
max_execution_time = 30
max_input_time = 60
max_input_vars = 1000
memory_limit = 128M
post_max_size = 8M
session.gc_maxlifetime = 1440
session.save_path = "/var/cpanel/php/sessions/ea-php71"
upload_max_filesize = 16M
zlib.output_compression = Off
cPanel
Home
Marken
Privacy Policy
Dokumentation
Hilfe